

Duraqua Rigid 320

■ matt 3401 - 320µm

Duraqua Medium Banner is a matt coated and tear-resistant rigid PVC film with a water-resistant coating for dye- and pigmented inks. The Product has a cardboard-like touch and the printouts are characterised by high color brilliance, high image definition and long durability. It is well suitable for various displays, pop-up-systems and presentations. The product is also suitable for short-term outdoor use when printed with pigmented inks.

Applications

- Indoor Signs
- Indoor short-term Promotions
- POP-up Displays
- Outdoor signage

Advantages

- Tear resistant rigid PVC-base
- Suitable for dye- and pigmented inks
- Water-resistant printouts with pigmented inks
- Suitable for short-term outdoor use
- Reduced memory effect, high rigidity
- Well suitable for lamination

Duraqua Rigid 320

■ matt 3401 - 320µm

List of Printers

Printer	Ink	Quality
Hewlett Packard DJ 5000 (PS) / 5500 (PS)	Dye	Excellent
Hewlett Packard DJ 5000 (PS)/ 5500(PS) UV+	Pigmented	Excellent
Hewlett Packard DJ 2000/2500/2800 3000/3500/3800 CP UV+	Pigmented	Excellent
Hewlett Packard DJ 4000 (PS), 1050C/1055CM	Dye (black pig)	Excellent
Hewlett Packard DJ 130	Dye	Good
Hewlett Packard DesignJet Z 2100 Vivera Pigment	Pigmented	Excellent
Hewlett Packard DesignJet Z 3100 Vivera Pigment	Pigmented	Excellent
Hewlett Packard DesignJet Z 6100 (PS) Vivera Pigment	Pigmented	Excellent
Encad Pro 600e/630/700/750 GS+	Dye	Excellent
Encad Pro 600e/630/700/750 GO+	Pigmented	Excellent
Epson Stylus Pro 7500 / 9500 ColorFast ink	Pigmented	Good
Epson Stylus Pro 7600 / 9600 UltraChrome™	Pigmented	Excellent
Epson Stylus Pro 10600 UltraChrome™ 1440x720dpi	Pigmented	Excellent
Epson Stylus Pro 4000-C8 UltraCrome ink	Pigmented	Excellent
Epson Stylus Pro 4800 UltraChrome K3	Pigmented	Excellent
Epson Stylus Pro 7800 / 9800 UltraChrome K3	Pigmented	Excellent
Canon W 6200 / 8200 pigmented ink	Pigmented	Good
Canon W 6400 / 8400 pigmented ink	Pigmented	Excellent
Canon imagePROGRAF 5000 / 8000 / 9000	Pigmented	Good

Last update: 21.06.2007

Duraqua Rigid 320

■ matt 3401 - 320µm

Physical Properties

Total weight	430g/m ²	ISO 536
Thickness	320µm	ISO 534

Conditions of Use and Stocking

The converting and storage should take place in a climate from 35 to 65% to relative humidity at a temperature from 10 to 30 C. Keep the product in the original packaging (cardboard box and PE bag). It is always recommended that cotton gloves be used when handling InkJet coated materials to avoid fingerprints.

The data provided in this product data sheet are values for orientation only.

Before using our print media please check their suitability for your printer and for your intended application. We do not take any liability for failures or damages resulting from technically modified printing inks and/or printers as technical specifications are subject to change.

16.02.2006