

ADHESIVE BACKED 2 MIL GLOSS POLYESTER LAMINATE

Won't shrink or expand; helps prevent tunneling or channeling
Polyester film for outstanding resistance to marking and scuffing

Construction

Product Number: KJ2POLYLAM
Adhesive: Clear Permanent Acrylic
Film: 2 mil Gloss Polyester
Liner: 1.2 mil Polyester
Gloss Level: 125 (avg.) @ 60°

Typical Performance Values

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

Durability: Outdoor - up to 2 years
Minimum Application Temperature: + 50° F (Minimum for Substrate)
Service Temperature Range: -65° F to +225° F
Chemical Resistance: Resistant to ammonium hydroxide - 10%,
antifreeze, detergent, distilled water, gasoline
and motor oil - SAE 20.

Typical Adhesion Values: 180° Peel Test
Substrate 15 min. 24 hrs.
Stainless Steel 3.2 lbs/in. 3.9 lbs/in.

Shelf Life: 2 years from ship date when stored in proper
conditions.