

ADHESIVE BACKED 5 MIL VELVET POLYCARBONATE LAMINATE

Non-glare, very high clarity film
High UV/Fade resistance
High scuff and abrasion resistance
Velvet surface hides scratches and fingerprints
Outstanding laminate for displays and point of purchase graphics

Construction

Product Number: KJ5VPC
Adhesive: Clear Permanent Acrylic
Film: 5 mil Polycarbonate
Liner: 1.5 mil Polyester
Gloss Level: 15 (avg.) @ 60°

Typical Performance Values

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

Durability: Outdoor - up to 2 years
Minimum Application Temperature: + 50° F (Minimum for Substrate)
Service Temperature Range: -30° F to +225° F
Chemical Resistance: Resistant to ammonium hydroxide - 10%,
detergent, distilled water, gasoline and
hydrochloric acid - 10%.

Typical Adhesion Values: 180° Peel Test

<u>Substrate</u>	<u>15 min.</u>	<u>24 hrs.</u>
5 mil	120 oz	140 oz

Shelf Life: 1 year from ship date when stored proper conditions.