

ADHESIVE BACKED 1 MIL DRY ERASE LAMINATE

For use with dry erase type markers
Laminate may be written on repeatedly; wipes clean with dry tissue or dry erase cleaning fluid
Readily laminates to any smooth sealed surface

Construction

Product Number:	KJERASELAM
Adhesive:	Clear Permanent Acrylic
Film:	1.0 mil Clear Polypropylene
Liner:	50 lb. paper
Gloss Level:	90 (avg.) @ 60°

Typical Performance Values

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

Durability:	Indoor Use Only
Minimum Application Temperature:	+ 50° F (Minimum for Substrate)
Service Temperature Range:	-40° F to +180° F (-46° C to + 82° C)
Chemical Resistance:	Resistant to ammonium hydroxide - 10%, detergent, distilled water, gasoline and hydrochloric acid - 10%.
Typical Adhesion Values:	PSTC-1 180° @ 12"/min Peel Test <u>15 min.</u> <u>24 hrs.</u> 30 oz. 40 oz.
Dimensional Stability:	No measurable shrinkage
Shelf Life:	2 years from ship date when stored in proper conditions.