

# ADHESIVE BACKED 2 MIL GLOSS CAST VINYL LAMINATE WITH POLYESTER LINER

UV protection added to vinyl  
Suitable for indoor and outdoor applications  
Designed for One Way Window Film on curved surfaces

## Construction

Product Number: KJGCLAM/POLY  
Adhesive: Clear Permanent Acrylic  
Film: 2 mil Premium Clear Cast Vinyl  
Liner: 1.2 mil Polyester  
Gloss Level: +80 (avg.) @ 60°

## Typical Performance Values

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

Durability: Outdoor - up to 5 years  
Minimum Application Temperature: + 40° F (Minimum for Substrate)  
Service Temperature Range: -50° F to 225° F  
Dimensional Stability: 0.01 in. (48 hrs. @ 150° F)  
Chemical Resistance: Resistant to alkalis, mild acids, most petroleum based oil, grease and aliphatic solvent and salts.

Typical Adhesion Values: 180° Peel Test

Substrate	20 min.	24 hrs.
Stainless Steel	32 oz/in	50 oz/in

UV Blocking: 200 nm - 360 nm at 100%      360 nm - 400 nm at 80%

Shelf Life: 1 year from ship date when stored in proper conditions.