

# OPTICALLY CLEAR MOUNTING FILM PERMANENT/PERMANENT


Applications -- window, glass doors or any transparent surface when see-through graphics are needed for promotional advertising and point of purchase in retailers; eye-catching exhibit booths at trade shows.

## Construction

Product Number: KJMOUNT/OPCLR  
Carrier: Optically Clear Polyester - 1 mil  
Adhesive: Optically Clear Permanent Solvent Acrylic  
Liner: One-Sided Silicone-Coated Polyester Film - 1.2 mil

## Product Scheme:

1 Liner  
2 Adhesive  
3 Carrier  
4 Adhesive  
5 Liner



## Typical Performance Values

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

Outdoor Durability: Up to 2 years

Typical Adhesion Values:

	180° Peel Test		
	<u>Substrate</u>	<u>15 min.</u>	<u>24 hrs.</u>
	Stainless Steel	35 oz	45 oz

Static Shear (1/2-inchx1/2-inchx500 grams) > 24 hours

Temperature: 50° F (Minimum for Substrate)

Service Temperature Range: -65° F to 225° F

Chemical Resistance: Resistant to detergent, gasoline, HCl - 10%, motor oil - SAE 20 and NH40H - 10%.

Shelf Life: 1 year from ship date when stored in proper conditions.