

ADHESIVE BACKED 3.2 MIL GLOSS WHITE VINYL REMOVABLE TINTED ADHESIVE FOR SOLVENT PRINTERS

Great when glare is not needed, black adhesive gives 100% opacity
Can be used for interior and exterior signage
Uses include outdoor signage, promotional and point of purchase graphics, trade show displays
Compatible with OEM Solvent and Mild Solvent Ink

Construction

Product Number:	SOL/WHTCAL/TINT/xxR wound print side out
Adhesive:	Tinted Black Removable Acrylic
Film:	3.2 mil Vinyl
Liner:	90 lb paper
Finish:	Gloss White
Gloss Level:	+ 65 (avg.) @ 60°

Typical Performance Values

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

Durability:	5 years Unprinted Printed outdoor - up to 2 years without lamination
Minimum Application Temperature:	+ 50° F (Minimum for Substrate)
Service Temperature Range:	-40° F to + 180° F (-46° C to + 82° C)
Chemical Resistance:	Resistant to alkalies, mild acids, most petroleum based oil, grease and aliphatic solvents and salts.
Typical Adhesion Values:	180° Peel Test <u>Substrate</u> <u>24 hrs.</u> Stainless Steel 1.0 lb/in
Shelf Life:	1 year from ship date when stored in proper conditions.